


AETHER XS 5.1 M

Ultra-Compact Low-Light
Monochrome Camera Core



APPLICATIONS

- Observation
- Enhanced vision system camera
- Security
- Homeland security
- Assistance
- Driving aid
 - Landscape camera

INNOVATIONS & FEATURES

- Ultra-compact
- Low-light conditions
- SDI and Analog output
- 2/3" 5.1 MP CMOS Global Shutter
- Full HD
- Dynamic Range > 74 dB
- E@SNR1 < 600 μ Lux
- Qualified for harsh environments

AETHER XS core,
Xtra Small for Low Light

SENSOR

TECHNOLOGY GEOMETRY	Pixel Size [H×V]	Resolution [H×V]	Resolution	Sensor Size
	3.45 μm × 3.45 μm	2464 × 2056	5.1 MP	8.5 mm × 7.093 mm
	Sensor Type	Mono/Color	Shutter	Max Image Circle
	CMOS	Mono	Global	11.07 mm

ELECTRO-OPTIC PERFORMANCE

EMVA	Qe @520nm	Read-out Noise	Saturation	Dynamic Range
	>65%	<2 e ⁻	>10,000 e ⁻	>74 dB
	SNR	DSNU	PRNU	E@ SNR1
	>40 dB	<1 e ⁻	<1%	600 μLux

INTERFACE

VIDEO COM POWER SYNCHRO	Control Interface	Power Supply	Video SDI	Analog Video
	RS485/422 GenICam XML File	7-28 Vdc	SMPTE 292 1080p 25-30-50-60 Hz or CXP 6.25 Gb/s	CCIR or RS170
	General I/O	Power Consumption	External Synchro	Coding
	3X RS485/422	3W	RS485/422	10 bit SMPTE 8-10-12 bit CXP

FUNCTIONS

BIT GAIN EXPOSURE CORRECTION DSP OPTIMIZATION	Built-in Test	Gain Control	Time Exposure Control	Gamma Correction
	PBIT- IBIT-CBIT	MGC -AGC	MEC-AEC	0.45 – 0.7 – 1 + blending mode
	Sensor Correction	Contrast Correction	H-V Flip	Noise Filter
	Blemish correction	Manual or Automatic DRC	Yes with no latency	N/A
	Binning Mode	Sharpness	Windowing	Non-uniformity Correction
	Digital ×2 ×4 ×8	Manual or automatic	ROI	Polynomial
	Color Calibration	White Balance	Debayer	Color Saturation
	N/A	N/A	N/A	N/A

HOUSING

MECHANICAL	Housing Size	Lens Mount	Weight	Input Filter
	35 × 35 × 20 mm ³	C-Mount	<80g	N/A

ENVIRONMENTAL / CONFORMITY

TEMPERATURE HUMIDITY SHOCKS VIBRATION EMI / EMC CE / IPC	Temperature	Humidity	Shocks	Vibration
	[-40°C – +71°C] functional	60% max	40g half sinus 11ms	4.5g rms [100Hz – 1,000Hz]
	EMI	EMC	Grounding	Acceptability
	CE (2014/30/EU)	CE (2014/30/EU)	<10mΩ	IPC-A610 Class3

PART NUMBER

P/N	SMPTE Video Output: LHC2M4N.6P05MNST30 CXP Video Output: LHC2M4N.6P05MNST31 Includes: Graphic Unit Interface (GUI), Video Cable, Pre-wired IO & Power Connector
-----	---

